

**SUPER HYDROPHOBIC COATED LENSES
"EZ Kleen AR"**

Advanced Coating Technology: This special coating utilizes thin film technology with a proprietary six-layer anti-reflective (A/R) coating applied to the anti-scratch coated lens then covered with an oleophobic layer that repels water, dust and fingerprints. Smudges just wipe off, making it very easy to clean and maintain the lenses.

1.49 Index (CR-39)

Minus on Minus											
SPH	-CYL										
	0.00	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00		
0.00											
0.25											
0.50											
0.75											
1.00											
1.25											
1.50											
1.75											
2.00											
2.25											
2.50											
2.75											
3.00											
3.25											
3.50											
3.75											
4.00											

NORMAL CYL
DIA 70 mm

1.61 Aspheric

Minus on Minus											
SPH	-CYL										
	0.00	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00		
0.00											
0.25											
0.50											
0.75											
1.00											
1.25											
1.50											
1.75											
2.00											
2.25											
2.50											
2.75											
3.00											
3.25											
3.50											
3.75											
4.00											
4.25											
4.50											
4.75											
5.00											
5.25											
5.50											
5.75											
6.00											
6.25											
6.50											
6.75											
7.00											
7.25											
7.50											
7.75											
8.00											

NORMAL CYL
DIA 75 mm

1.67 Aspheric

Minus on Minus											
SPH	-CYL										
	0.00	0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00		
0.00											
0.25											
0.50											
0.75											
1.00											
1.25											
1.50											
1.75											
2.00											
2.25											
2.50											
2.75											
3.00											
3.25											
3.50											
3.75											
4.00											
4.25											
4.50											
4.75											
5.00											
5.25											
5.50											
5.75											
6.00											
6.25											
6.50											
6.75											
7.00											
7.25											
7.50											
7.75											
8.00											
8.25											
8.50											
8.75											
9.00											
9.25											
9.50											
9.75											
10.00											

NORMAL CYL
DIA 75 mm